## NSN 5935-01-614-6430

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-614-6430 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.838 inches **Overall Height:** 1.453 inches **Overall Width:** 1.453 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** 0.447 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20-41 single mating end **Contact Removability:** Removable single mating end single contact grouping **Insert Position In Deg:** 95.0 and 132.0 and 232.0 and 260.0 and 330.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Cord grip **End Application: Operating Tempurature Rating:** Between -55.0 degrees celsius and 200.0 degrees celsius Thready Qty Per Inch (tpi): 18 **Thread Size:** 

1.188 inches

## NSN 5935-01-614-6430

Electrical Receptacle Connector - Page 2 of 2



| Terminal Location:   |
|--|
| Back single mating end single contact grouping   |
| Terminal Type:   |
| Crimp single mating end single contact grouping  |
| Shell Material:  |
| Aluminum alloy   |
| Shell Surface Treatment:   |
| Nickel   |
| Included Contact Quantity:   |
| 41 single mating end single contact grouping   |
| Included Contact Type:   |
| Round pin single mating end single contact grouping  |
| Product Name:  |
| Connector, receptacl   |
| Special Features:  |
| Shell style: wall mount receptacle (back panel mounting)shell size: 20   |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Thread Series Designator:  |
| Unef   |
| Specification Data:  |
| 96906-ms27497 government standard  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
|  |
|  |