

View Online at <https://aerobasegroup.com/nsn/5935-01-614-7665>

**Body Style:**

Straight shape, internal coupling

**Environmental Protection:**

Vibration resistant and shock resistant and thermal shock resistant and moisture resistant and corrosion resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Rf single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Frequency Rating:**

6.0 gigahertz single mating end single contact grouping

**Connector Cable Strain Relief Method:**

Crimp type

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**End Application:**

Kc-135 blk 45

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

For ecs cable

**Precious Material And Location:**

Shell and contact plating gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0