NSN 5935-01-614-8692

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-614-8692

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

34.7 millimeters

Overall Diameter:

34.9 millimeters

Distance From Mounting Shoulder To Front Face:

22.6 millimeters

Mounting Facility Thickness:

Between 1.5 millimeters and 3.2 millimeters

Threaded Device Type:

Back shell and coupling facility and hub

Mating End Quantity:

1

Contact Position Arrangement Style:

Ahac 11-99 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 68.0 and 178.0 and 204.0 and 247.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Tempurature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Thread Size:

15.0 millimeters and 0.750 inches and 20.0 millimeters

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

NSN 5935-01-614-8692

Electrical Receptacle Connector - Page 2 of 2



Thread Tolerance Class:
6g external
ncluded Contact Quantity:
7 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contacts per m39029/56-351
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
31349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
so m and special acme and iso m
Specification Data:
31349-mil-dtl-38999/24 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4039b0