NSN 5935-01-615-0152

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-615-0152

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

34.7 millimeters

Overall Diameter:

44.5 millimeters

Distance From Mounting Shoulder To Front Face:

22.6 millimeters

Mounting Facility Thickness:

Between 1.5 millimeters and 3.2 millimeters

Threaded Device Type:

Back shell and coupling facility and hub

Mating End Quantity:

1

Contact Position Arrangement Style:

17-99 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 67.0 and 164.0 and 218.0 and 280.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Tempurature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Thread Size:

25.0 millimeters and 1.188 inches and 32.0 millimeters

Terminal Location:

Back single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

NSN 5935-01-615-0152

Electrical Receptacle Connector - Page 2 of 2



Thread Tolerance Class:
6g external
Included Contact Quantity:
21 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
Contacts per m39029/56-352 and -351
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m and special acme and iso m
Specification Data:
81349-mil-dtl-38999/24 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Filig:
A039b0