NSN 5935-01-615-1063

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-615-1063 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.662 inches **Overall Height:** 2.750 inches **Overall Width:** 2.750 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.188 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 40-62 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 140.0 Shell Type: **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 16 **Thread Size:** 2.500 inches **Terminal Location:** Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-615-1063

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
60 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contacts per m39029/45-295
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-5015 spec.