## NSN 5935-01-615-6680

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-615-6680

**Body Style:** Straight shape, external coupling **Overall Length:** 1.40 inches **Overall Height:** 2.25 inches **Overall Width:** 2.25 inches **Unthreaded Mounting Hole Diameter:** 0.173 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.75 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 1.75 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Mating End Quantity: Contact Position Arrangement Style:** 32-5 single mating end **Connector Locking Method:** Bayonet slot **End Application:** 2355-01-598-5731 **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 

Included Contact Type:

Round socket single mating end single contact grouping

2 single mating end single contact grouping

## NSN 5935-01-615-6680

Electrical Receptacle Connector - Page 2 of 2



Special Features:
The finish is 500 hour salt spray resistant.
Color:
Olive drab
Precious Material And Location:
Contact plating silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A039b0