

View Online at <https://aerobasegroup.com/nsn/5935-01-615-6689>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

33.7 millimeters

**Overall Height:**

31.0 millimeters

**Overall Width:**

31.0 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 23.0 millimeters and 24.6 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 23.0 millimeters and 24.6 millimeters

**Distance From Mounting Shoulder To Front Face:**

20.8 millimeters

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Arbq 15-15 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0 and 124.0 and 152.0 and 219.0 and 265.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 175.0 degrees celsius

**Thread Size:**

22.0 millimeters and 1.000 inches

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Thread Tolerance Class:**

6g external

**Test Data Document:**

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Iso m and special acme

**Specification Data:**

81349-mil-dtl-38999/20 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0