

View Online at <https://aerobasegroup.com/nsn/5935-01-615-6701>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

37.5 millimeters

Overall Height:

39.7 millimeters

Overall Width:

39.7 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 29.3 millimeters and 31.8 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 29.3 millimeters and 31.8 millimeters

Distance From Mounting Shoulder To Front Face:

20.0 millimeters

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

AEEP 21-75 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 50.0 and 160.0 and 190.0 and 225.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Temperature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Thread Size:

31.0 millimeters and 1.375 inches

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Thread Tolerance Class:

6g external

Test Data Document:

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme

Specification Data:

81349-mil-dtl-38999/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0