

View Online at <https://aerobasegroup.com/nsn/5935-01-615-7368>

Thread Class:

E2

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.781 inches

Terminal Length:

0.974 inches single mating end single contact grouping

Bushing Diameter:

0.625 inches

Overall Diameter:

Between 0.850 inches and 0.900 inches

Distance From Mounting Shoulder To Front Face:

Between 0.912 inches and 0.940 inches

Mounting Facility Thickness:

0.250 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11.0 gigahertz single mating end single contact grouping

Connector Locking Method:

Internally threaded coupling ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

F/a18-e/f

Width Across Flats:

Between 0.532 inches and 0.543 inches

Thready Qty Per Inch (tpi):

A24.0

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Thread Tolerance Class:

2a external

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Coaxial pin single mating end single contact grouping

Product Name:

Connectot, plug

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0