NSN 5935-01-615-8071

Thread Class:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-615-8071

Tilleau Class.
2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
33.2 millimeters
Overall Diameter:
41.7 millimeters
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Zaab 21-11 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key or multiple key
Insert Position In Deg:
0.0 and 135.0 and 170.0 and 200.0 and 310.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Operating Tempurature Rating:
Between -65.0 degrees celsius and 175.0 degrees celsius
Thread Size:
31.0 millimeters and 1.375 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Plastic
Shell Surface Treatment:
Cadmium
Thread Tolerance Class:
6g external
Included Contact Quantity:

Included Contact Quantity:

11 single mating end single contact grouping

NSN 5935-01-615-8071

Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per m39029/56-353
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m and special acme
Specification Data:
81349-mil-dtl-38999/26 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0