

View Online at <https://aerobasegroup.com/nsn/5935-01-615-8639>

Body Style:

Straight shape, external coupling

Overall Length:

18.0 millimeters

Bushing Diameter:

15.0 millimeters

Overall Height:

15.0 millimeters

Overall Width:

15.0 millimeters

Unthreaded Mounting Hole Diameter:

9.2 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

9.5 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

10.5 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

2.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Connector Locking Method:

Shell twistlock

End Application:

5980-01-591-7588

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Nickel and gold single mating end single contact grouping

Insert Material:

Resin synthetic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Zinc alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Circular connectors r01, r03, r05 mfr ref all treatment responses

Shell Material Specification:

Circular connectors r01, r03, r05 mfr ref all material responses

Insert Material Specification:

UI standard class 94v-0 national std/spec single material response single mating end

Included Contact Quantity:

2 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Product Name:

15093 connector, receptacle, electrical

Color:

Natural

Precious Material And Location:

Coating on contacts gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0