NSN 5935-01-615-8815

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-615-8815

Body Style:

Straight shape, external coupling

Overall Length:

Between 0.370 inches and 0.380 inches

Overall Height:

Between 0.307 inches and 0.317 inches

Overall Width:

Between 0.542 inches and 0.582 inches

Environmental Protection:

Thermal shock resistant and corrosion resistant and shock resistant and vibration resistant and moisture resistant

Distance From Mounting Shoulder To Front Face:

Between 0.300 inches and 0.320 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

5865-01-567-8646

Operating Tempurature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and nickel and copper single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and nickel and copper

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Product Name:

Jack assembly, end launch, sma

NSN 5935-01-615-8815

Electrical Receptacle Connector - Page 2 of 2



Precious	Material	∆nd ∣	Location:
riccious	iviale lai	Allu I	LUCALIUII.

Contact and shell plating gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0