NSN 5935-01-616-3692

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-616-3692 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.662 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.938 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.938 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36a66 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Key or multiple key **Insert Position In Deg:** 250.0 Shell Type: **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 16 **Thread Size:** 2.250 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper single mating end all contact groupings

NSN 5935-01-616-3692

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Silver single mating end 2nd contact grouping
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
52 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
Contacts per m39029/44-287 and -289
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material:
Gold and silver
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-5015 spec.