NSN 5935-01-618-3443

Thread Class: 2a and 2a

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-618-3443

Za aliu Za
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
5.375 inches
Overall Diameter:
1.599 inches
Cable Entrance Diameter:
Between 0.500 inches and 0.750 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-22 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key or multiple key
Insert Position In Deg:
Insert Position In Deg: 0.0
0.0
0.0 Shell Type:
0.0 Shell Type: Solid
0.0 Shell Type: Solid Connector Locking Method:
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method:
O.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp
O.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi):
O.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 18 and 18
Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 18 and 18 Thread Size:
O.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 18 and 18 Thread Size: 1.313 inches and 1.378 inches
Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 18 and 18 Thread Size: 1.313 inches and 1.378 inches Terminal Location:
Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 18 and 18 Thread Size: 1.313 inches and 1.378 inches Terminal Location: Back single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 18 and 18 Thread Size: 1.313 inches and 1.378 inches Terminal Location: Back single mating end single contact grouping Terminal Type:
Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 18 and 18 Thread Size: 1.313 inches and 1.378 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 18 and 18 Thread Size: 1.313 inches and 1.378 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material:
Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 18 and 18 Thread Size: 1.313 inches and 1.378 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy

NSN 5935-01-618-3443

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity: 4 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Contacts per m39029/45-298 **Precious Material And Location:** Contact surface silver **Precious Material:** Silver **Thread Series Designator:** Unef and unef Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Mil-dtl-5015 spec.

Mil-std (military Standard):

Fiig: A039b0