

View Online at <https://aerobasegroup.com/nsn/5935-01-618-4019>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Angle shape w/cable clamp

Overall Diameter:

1.312 inches

Body Angle In Deg:

90.0

Cable Entrance Diameter:

Between 0.344 inches and 0.562 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

15-21 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key or multiple key

Insert Position In Deg:

0.0 and 135.0 and 170.0 and 200.0 and 310.0

Shell Type:

Solid

Connector Cable Strain Relief Method:

Cable clamp

Distance From Centerline To Connector End:

3.431 inches

Distance From Centerline To Cable End:

3.087 inches

Thready Qty Per Inch (tpi):

20 and 10

Thread Size:

1.000 inches and 1.072 inches

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

21 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Contacts per m39029/83-508

Color:

Olive drab

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-dtl-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and double stub

Specification Data:

81349-mil-dtl-28840/28 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0