NSN 5935-01-618-5884

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-618-5884 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/cable clamp **Overall Length:** 56.0 millimeters **Bushing Diameter:** 1.0 inches **Overall Height:** Between 32.2 millimeters and 32.8 millimeters **Overall Width:** Between 32.2 millimeters and 32.8 millimeters **Unthreaded Mounting Hole Diameter:** 3.1 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 24.5 millimeters and 24.7 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 24.5 millimeters and 24.7 millimeters **Distance From Mounting Shoulder To Front Face:** Between 13.8 millimeters and 14.6 millimeters **Mating End Quantity: Contact Position Arrangement Style:** 16s-8 single mating end **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Cable clamp **End Application:** 2320-01-544-2244 Thready Qty Per Inch (tpi): 20 **Thread Size:** 1.0 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

NSN 5935-01-618-5884

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber synthetic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Color:
Olive drab
Precious Material And Location:
Contact plating silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
_