

View Online at <https://aerobasegroup.com/nsn/5935-01-618-7694>

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

1.500 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.718 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.718 inches

Distance From Mounting Shoulder To Front Face:

0.900 inches

Mounting Facility Thickness:

0.060 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma 1st mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Frequency Rating:

18.0 gigahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

End Application:

Interface unit

Thready Qty Per Inch (tpi):

36 and 24

Thread Size:

0.250 inches and 0.625 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Shell Material:

Stainless steel

Included Contact Quantity:

2 all mating ends all contact groupings

Included Contact Type:

Coaxial pin all mating ends all contact groupings

Product Name:

Adapter, connector

Precious Material And Location:

Center contact plating gold

Precious Material:

Gold

Specification Data:

Mil-std-348 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-std-348 spec.