NSN 5935-01-618-8696

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-618-8696 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.349 inches **Overall Height:** 1.219 inches **Overall Width:** 1.219 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** 0.820 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Aubc 15-18 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 21.0 and 105.0 and 132.0 and 220.0 and 265.0 Shell Type: **Connector Locking Method:** Bayonet pin **End Application:** B₁b **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius Thready Qty Per Inch (tpi): 20

Thread Size:

0.813 inches

NSN 5935-01-618-8696

Electrical Receptacle Connector - Page 2 of 2



Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy	
Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy	
Crimp single mating end single contact grouping Shell Material: Aluminum alloy	
Shell Material: Aluminum alloy	
Aluminum alloy	
Shall Surface Treatment	
Shell Surface Treatment:	
Nickel	
Included Contact Quantity:	
18 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Special Features:	
Contacts per m39029/58-363	
Precious Material And Location:	
Contact surface gold	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificat	ior
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unef	
Specification Data:	
96906-ms27656 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-dtl-38999 spec.	