NSN 5935-01-618-9112

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-618-9112 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.349 inches **Overall Height:** 1.031 inches **Overall Width:** 1.031 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Distance From Mounting Shoulder To Front Face:** 0.820 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 23-98 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 105.0 and 132.0 and 220.0 and 265.0 and 346.0 Shell Type: **Connector Locking Method:** Bayonet pin **End Application:** B₁b **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius Thready Qty Per Inch (tpi): 24

Thread Size:

0.563 inches

NSN 5935-01-618-9112

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per m39029/58-363
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27656 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-38999 spec.