Electrical Connector Jackscrew - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-618-9955

Inrea Class: 2a Thread Direction: Right-hand Overall Length: 2.550 inches Overall Diameter: 0.600 inches Thread Length: 0.600 inches Mounting Facility Type And Quantity: 1 jackscrww Thready Qty Per Inch (tpl): 24 Thread Size: 0.188 inches Material: Stel, corrosion resisting Material: Stel, corrosion resisting Mater				
Thread Direction:         Right-hand         Overall Length:         2.50 inches         Overall Diameter:         0.361 inches         Thread Length:         0.500 inches         Mounting Facility Type And Quantity:         1 jackscrew         Thread Size:         1 jackscrew         Thread Size:         0.188 inches         Material:         Stel, corrosion resisting         Material:         Statinless steel         Surface Treatment:         Passivate         Starke Treatment:         Passivate         Thread Starke:         Starke Treatment:         Passivate         Thread Starke:         Starke Treatment:         Passivate <th>Thread Class:</th> <th></th> <th></th> <th></th>	Thread Class:			
Right-hand         Overall Length:         2.500 inches         Overall Diameter:         0.361 inches         Thread Length:         0.500 inches         Mounting Facility Type And Quantity:         1 jackscrew         Thread Qt Per Inch (tpl):         24         Thread Size:         0.188 inches         Material:         Stainless steel         Surface Treatment:         Passivate         Stafe Treatment:         Passivate         Stafe Treatment:         Passivate         Thread Size:         Other Size:         Other Size:         Other Size:         Other Size:         Passivate         Then				
Nevrall Length:2.550 inchesOverall Diameter:0.361 inchesThread Length:0.500 inchesMounting Facility Type And Quantity:1 jackscrewThready Qty Per Inch (tpi):24Thread Size:0.186 inchesMaterial:Steel, corrosion resistingMaterial:Stainless steelStafface Treatment:PassivateSturface Treatment:PassivateSturface Treatment:PassivateChread Series Designator:UnicChread Series Designator:NaNaStoff Left:NaStoff Left:Stoff Left:Stof				
250 inches Overall Diameter: Overall Diameter: Overall Diameter: Overall Diameter: Overall Compose Diameter: Overall Compose Diameter: Overall Compose Diameter: Diame				
Overall Diameter:0.361 inchesThread Length:0.500 inchesMounting Facility Type And Quantity:1 jackscrewThready Qty Per Inch (tpi):24Thread Size:0.188 inchesMaterial:Steel, corrosion resistingMaterial:Starles steelSturface Treatment:PassivateStyle Designator:Body MountedPassivateThread Size:Out of the Size:Style Designator:Body MountedDurated Size:PassivateThread Size:NaStyle Designator:PassivateDiread Size:Diread Size:NaStarle:NaDiread Size:Diread Size:NaStarle:NaStarle:NaStarle:NaStarle:NaStarle:S				
0.361 inches         Thread Length:         0.500 inches         Mounting Facility Type And Quantity:         1 jackscrew         Thready Oty Per Inch (tpi):         24         Thread Size:         0.188 inches         Material:         Stel, corosion resisting         Material:         Stainless stel         Striface Treatment:         Passivate         Style Designator:         Icade Size Signator:         Passivate         Thread Size Signator:         Passivate         Thread Size Signator:         Passivate         Thread Size Signator:         Passivate         Thread Size Signator:         Pasivate         Size Size Size Signator:<				
Thread Length:         0.500 inches         Mounting Facility Type And Quantity:         1 jackscrew         Thready Qty Per Inch (tpi):         24         Thread Size:         0.188 inches         Material:         Steel, corrosion resisting         Material:         Stainless steel         Strikee Treatment:         Passivate         Style Designator:         Rody mounted         Thread Steils         Strikee Treatment:         Passivate         Style Designator:         It of Masure:         Passivate         Thread Strike:         Passivate         Strike:         Passivate         St				
0.500 inches         Mounting Facility Type And Quantity:         1 jackscrew         Thready Qty Per Inch (tpi):         24         Thread Size:         0.188 inches         Material:         Steel, corrosion resisting         Material:         Stainless steel         Stainless steel         Style Designator:         Passivate         Starface Treatment:         Passivate         Sturface Treatment:         Passivated         Sturface Treatment:         Passivated         Sturface Treatment:         Passivated         Thread Stries Designator:         Unc         Stoff Measure:         Inc         Stoff Measure: <tr< th=""><th></th><th></th><th></th><th></th></tr<>				
Nounting Facility Type And Quantity:1 jackscrewThready Qty Per Inch (tpi):2424Thread Size:0.188 inchesMaterial:Steel, corrosion resistingMaterial:Stainless steelStriface Treatment:PassivateStyle Designator:Body mountedStarface Treatment:PassivateSturface Treatment:PostivateBody mountedSturface Treatment:PostivateDesignator:UncSturface Treatment:PassivatedThread Series Designator:UncSturface Treatment:NaDit of Measure:Fig:Fig:				
1 jackscrew         Thread Qty Per Inch (tpi):         24         Thread Size:         0.188 inches         Material:         Steel, corrosion resisting         Material:         Stainless steel         Surface Treatment:         Passivate         Style Designator:         Body mounted         Straface Treatment:         Passivate         Straface Treatment:         Passivate         Straface Treatment:         Passivated         Straface Treatment:         Passivated         Thread Series Designator:         Unc         Sheff Life:         Na         Dit Of Measure:         Tomelitarization:         No         Fig:	0.500 inches			
Thready Quy Per Inch (tpi):2424Thread Size:0.188 inchesMaterial:Steel, corrosion resistingMaterial:Stainless steelSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment:PassivateDurited Series Designator:UncShelf Life:NaUnt Of Measure:	Mounting Facility Type And Q	uantity:		
24 Fread Size: 0.188 inches Material: Steel, corrosion resisting Material: Stainless steel Surface Treatment: Passivate Surface Treatment: Passivated Tread Series Designator: Unc Sheff Life: Na Sheff Life: Na Fig: i Li Di Measure: Jon Fig:	1 jackscrew			
Thread Size:0.188 inchesMaterial:Steel, corrosion resistingMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:Body mountedSurface Treatment:PassivatedDurface Treatment:PassivatedDurface Treatment:PassivatedDurface Treatment:PassivatedDurface Treatment:PassivatedDurface Treatment:PassivatedDurface Treatment:UncSuff Life:N/aUnt Of Measure:Demilitarization:NoFig:	Thready Qty Per Inch (tpi):			
0.188 inchesMaterial:Steel, corrosion resistingMaterial:Material:Stainless steelSurface Treatment:PassivateSurface Treatment:Body mountedSurface Treatment:PassivatedThread Series Designator:UncShelf Life:N/aDenilitarization:ToFormilitarization:NoFig:	24			
Material:Steel, corrosion resistingMaterial:Material:Stainless steelSurface Treatment:PassivateBody mountedSurface Treatment:PassivatedThread Series Designator:UncShelf Life:NaDint of Measure:Penilitarization:NoFig:	Thread Size:			
Steel, corrosion resistingMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:Body mountedSurface Treatment:PassivatedThread Series Designator:UncShelf Life:N/aUnt Of Measure:-Demiltarization:NoFig:	0.188 inches			
Material:Stainless steelSurface Treatment:PassivateStyle Designator:Body mountedSurface Treatment:PassivatedThread Series Designator:UncShelf Life:N/aDint Of Measure:-Demilitarization:NoFig:	Material:			
Stainless steelSurface Treatment:PassivateStyle Designator:Body mountedSurface Treatment:PassivatedThread Series Designator:UncShelf Life:N/aDit of Measure:MoFine:NoFig:	Steel, corrosion resisting			
Surface Treatment:PassivateStyle Designator:Body mountedSurface Treatment:PassivatedThread Series Designator:UncShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Material:			
PassivateStyle Designator:Body mountedSurface Treatment:PassivatedThread Series Designator:UncShelf Life:N/aDint Of Measure:Demilitarization:NoFig:	Stainless steel			
Style Designator:Body mountedBurface Treatment:PassivatedThread Series Designator:UncShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Surface Treatment:			
Body mountedSurface Treatment:PassivatedThread Series Designator:UncShelf Life:N/aDut Of Measure:Demilitarization:NoFig:	Passivate			
Surface Treatment:PassivatedThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Style Designator:			
Passivated Thread Series Designator: Unc Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body mounted			
Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Surface Treatment:			
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Passivated			
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Thread Series Designator:			
N/a Unit Of Measure:  Demilitarization: No Fiig:	Unc			
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:			
 Demilitarization: No Fiig:	N/a			
Demilitarization: No Fiig:	Unit Of Measure:			
No Fiig:				
Fiig:	Demilitarization:			
	No			
A10100	Fiig:			
	A10100			