

View Online at <https://aerobasegroup.com/nsn/5935-01-620-2503>

**Body Style:**

Straight shape w/clamp, grounded

**Cable Entrance Diameter:**

Between 0.220 inches and 0.660 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"3, 5-20" single mating end

**Contact Maximum Current Rating In Amps:**

20.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Polarization Method:**

Contact

**Shell Type:**

Split

**Connector Locking Method:**

Friction

**Connector Cable Strain Relief Method:**

Cord grip

**End Application:**

Link 16 alask

**Features Provided:**

Grounded contact

**Terminal Location:**

Side single mating end all contact groupings

**Terminal Type:**

Screw w/wire lock single mating end all contact groupings

**Shell Material:**

Plastic polyamide

**Included Contact Quantity:**

3 single mating end all contact groupings

**Included Contact Type:**

T-pin single mating end 1st contact grouping

**Product Name:**

2 pole, 3 wire, insulated, grounding plug

**Special Features:**

Body is impact and crush resistant. The split shell is hinged at one end and has removable cord inserts at the other end.

**Color:**

Black

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0