

View Online at <https://aerobasegroup.com/nsn/5935-01-620-2503>

Body Style:

Straight shape w/clamp, grounded

Cable Entrance Diameter:

Between 0.220 inches and 0.660 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 5-20" single mating end

Contact Maximum Current Rating In Amps:

20.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Split

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Cord grip

End Application:

Link 16 alask

Features Provided:

Grounded contact

Terminal Location:

Side single mating end all contact groupings

Terminal Type:

Screw w/wire lock single mating end all contact groupings

Shell Material:

Plastic polyamide

Included Contact Quantity:

3 single mating end all contact groupings

Included Contact Type:

T-pin single mating end 1st contact grouping

Product Name:

2 pole, 3 wire, insulated, grounding plug

Special Features:

Body is impact and crush resistant. The split shell is hinged at one end and has removable cord inserts at the other end.

Color:

Black

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0