Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-620-2611

# **Body Style:** Straight shape, external coupling **Overall Length:** Between 0.484 inches and 0.948 inches **Overall Height:** Between 1.230 inches and 1.250 inches **Overall Width:** Between 1.230 inches and 1.250 inches **Environmental Protection:** Fungus resistant **Unthreaded Mounting Hole Diameter:** Between 0.182 inches and 0.192 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.807 inches and 0.817 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.807 inches and 0.817 inches **Distance From Mounting Shoulder To Front Face:** Between 0.185 inches and 0.362 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 6 single mating end **Polarization Method:** Key or multiple key **End Application:** Sincgars v **Operating Tempurature Rating:** Between -55.0 degrees celsius and 85.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Aluminum alloy

## **Shell Surface Treatment:**

Cadmium and chromate

### **Included Contact Quantity:**

6 single mating end single contact grouping



Included Contact Type:

Round pin single mating end single contact grouping

Color:

Olive drab

Precious Material And Location:

Contact plating gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0