

View Online at <https://aerobasegroup.com/nsn/5935-01-620-3656>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

30.30 millimeters

Cable Entrance Diameter:

3.1 millimeters

Distance From Mounting Shoulder To Front Face:

18.00 millimeters

Mounting Facility Thickness:

3.5 millimeters

Threaded Device Type:

Mounting bushing and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Crimp type

End Application:

Link 16 alaska

Width Across Flats:

17.50 millimeters

Thready Qty Per Inch (tpi):

28 and 28

Thread Size:

0.500 inches and 0.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact plating gold

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0