

View Online at <https://aerobasegroup.com/nsn/5935-01-621-6909>

Body Style:

Straight shape w/o clamp

Environmental Protection:

Watertight

Mating End Quantity:

1

Contact Position Arrangement Style:

L14-30 single mating end

Contact Maximum Current Rating In Amps:

30.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Contact twistlock

Connector Cable Strain Relief Method:

Cord grip

End Application:

2330-01-580-7654

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Nickel single mating end all contact groupings

Insert Material:

Plastic polyamide single mating end

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Rubber

Included Contact Quantity:

4 single mating end all contact groupings

Included Contact Type:

Curved socket w/lock single mating end 3rd contact grouping

Special Features:

Is rohs compliant. Is a 3 pole/4 wire type.

Color:

Yellow

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0