

View Online at <https://aerobasegroup.com/nsn/5935-01-621-6909>

**Body Style:**

Straight shape w/o clamp

**Environmental Protection:**

Watertight

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

L14-30 single mating end

**Contact Maximum Current Rating In Amps:**

30.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

250.0 single mating end all contact groupings

**Polarization Method:**

Contact

**Connector Locking Method:**

Contact twistlock

**Connector Cable Strain Relief Method:**

Cord grip

**End Application:**

2330-01-580-7654

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Nickel single mating end all contact groupings

**Insert Material:**

Plastic polyamide single mating end

**Terminal Type:**

Screw single mating end all contact groupings

**Shell Material:**

Rubber

**Included Contact Quantity:**

4 single mating end all contact groupings

**Included Contact Type:**

Curved socket w/lock single mating end 3rd contact grouping

**Special Features:**

Is rohs compliant. Is a 3 pole/4 wire type.

**Color:**

Yellow

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0