

View Online at <https://aerobasegroup.com/nsn/5935-01-621-7098>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

0.88 inches

**Overall Diameter:**

0.31 inches

**Cable Entrance Diameter:**

0.07 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

115.0 degrees celsius

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Terminal Location:**

Back single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Round socket single mating end single contact grouping

**Product Name:**

Insulated miniature banana jack.

**Special Features:**

Mounts in panels up to 0.25 inches thick. The panel insulator material is polycarbonate. Includes a hex nut and lockwasher.

**Color:**

Blue

**Precious Material And Location:**

Body plating gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0