

View Online at <https://aerobasegroup.com/nsn/5935-01-621-7102>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

0.88 inches

Overall Diameter:

0.31 inches

Cable Entrance Diameter:

0.07 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Connector Locking Method:

Friction

Operating Temperature Rating:

115.0 degrees celsius

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Terminal Location:

Back single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round socket single mating end single contact grouping

Product Name:

Insulated miniature banana jack.

Special Features:

Mounts in panels up to 0.25 inches thick. The panel insulator material is polycarbonate. Includes a hex nut and lockwasher.

Color:

White

Precious Material And Location:

Body plating gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0