

View Online at <https://aerobasegroup.com/nsn/5935-01-623-7854>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

0.934 inches

Overall Diameter:

1.766 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

24-4 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Key or multiple key

Insert Position In Deg:

0.0 and 100.0 and 128.0 and 228.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

End Application:

B-1

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Thready Qty Per Inch (tpi):

18

Thread Size:

1.438 inches

Terminal Location:

Back single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Included Contact Quantity:

8 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Special Features:

Contacts per m39029/58-364 and -363

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27484 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.