NSN 5935-01-624-1779

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-624-1779 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.248 inches **Overall Diameter:** Between 1.609 inches and 1.641 inches **Distance From Mounting Shoulder To Front Face:** Between 0.910 inches and 0.920 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 15-19 single mating end **Polarization Method:** Key or multiple key **Connector Locking Method:** Bayonet pin **End Application:** Unit 5 fc 8 Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel

Included Contact Quantity:

19 single mating end single contact grouping

NSN 5935-01-624-1779

Electrical Receptacle Connector - Page 2 of 2



ın	ادام	ided	0	nto	~+	т.,	-
m	CIU	ıaea		mta	Ct	ıν	De:

Round socket single mating end single contact grouping

Special Features:

The finish is 500 hour salt spray resistant.

Precious Material And Location:

Contact plating gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0