NSN 5935-01-624-5685

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-624-5685

Thread Class: 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 34.2 millimeters **Overall Height:** 31.0 millimeters **Overall Width:** 31.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 23.0 millimeters and 24.6 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 23.0 millimeters and 24.6 millimeters **Distance From Mounting Shoulder To Front Face:** 19.5 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 15-15 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 124.0 and 152.0 and 219.0 and 265.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Operating Tempurature Rating:** Between -65.0 degrees celsius and 175.0 degrees celsius

Thread Size:

22.0 millimeters and 1.000 inches

Terminal Location:

Back single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

NSN 5935-01-624-5685

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Plastic
Shell Surface Treatment:
Cadmium
Thread Tolerance Class:
6g external
ncluded Contact Quantity:
14 single mating end 2nd contact grouping
ncluded Contact Type:
Round socket single mating end all contact groupings
Test Data Document:
31349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
so m and special acme
Specification Data:
31349-mil-dtl-38999/20 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A039b0