

View Online at <https://aerobasegroup.com/nsn/5935-01-624-5693>

Body Style:

Straight shape, external coupling strain relief

Overall Length:

60.0 millimeters

Overall Height:

Between 32.2 millimeters and 32.8 millimeters

Overall Width:

Between 32.2 millimeters and 32.8 millimeters

Environmental Protection:

Shock proof and vibration proof and solvent resistant

Unthreaded Mounting Hole Diameter:

4.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 24.5 millimeters and 24.7 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 24.5 millimeters and 24.7 millimeters

Distance From Mounting Shoulder To Front Face:

Between 18.2 millimeters and 18.6 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

18-10 single mating end

Contact Maximum Current Rating In Amps:

41.0 single mating end single contact grouping

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Cable clamp

End Application:

5895-01-583-6735

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

The insert material is polychloroprene. Has quarter turn bayonet locking mechanism.

Color:

Olive drab

Precious Material And Location:

Contact plating silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0