

View Online at <https://aerobasegroup.com/nsn/5935-01-624-5811>

**Thread Class:**

2b

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

46.1 millimeters

**Overall Diameter:**

46.9 millimeters

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

9-35 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Key or multiple key

**Insert Position In Deg:**

0.0 and 105.0 and 140.0 and 215.0 and 265.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**End Application:**

2350-00-122-6826

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 175.0 degrees celsius

**Thread Size:**

12.0 millimeters and 0.625 inches

**Terminal Location:**

Back single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Thread Tolerance Class:**

6g external

**Included Contact Quantity:**

6 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Product Name:**

Connector, electrical, circular, threaded, plug, lanyard release, fail-safe, removable crimp contacts, pins, series iii.

**Special Features:**

Contacts m39029/58-360

**Precious Material And Location:**

Contact surface gold

**Precious Material:**

Gold and gold

**Test Data Document:**

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Iso m and special acme

**Specification Data:**

81349-mil-dtl-38999/26 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0