Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-624-6620

### **Body Style:**

Straight shape w/flange

### **Bushing Diameter:**

1.72 inches

# **Overall Diameter:**

2.56 inches

#### **Distance From Mounting Shoulder To Rear Face:**

1.72 inches

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

"3, 5-15" single mating end

### **Contact Maximum Current Rating In Amps:**

15.0 single mating end all contact groupings

### **Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end all contact groupings

### **Polarization Method:**

Contact

### **Connector Locking Method:**

Friction

### End Application:

C5m amp se

### Operating Tempurature Rating:

Between -40.0 degrees celsius and 75.0 degrees celsius

### **Features Provided:**

Grounded contact

### **Terminal Location:**

Side single mating end all contact groupings

### **Contact Material:**

Copper alloy single mating end all contact groupings

#### **Terminal Type:**

Screw single mating end all contact groupings

### Shell Material:

Plastic polyamide and plastic polycarbonate

### Included Contact Quantity:

3 single mating end all contact groupings

# Included Contact Type:

Flat socket single mating end 1st contact grouping

Color:

White

#### Shelf Life:

N/a

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0