Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-625-5616

## Body Style:

Straight shape duplex

## Mating End Quantity:

2

## **Contact Position Arrangement Style:**

"3, 5-15" all mating ends

### **Contact Maximum Current Rating In Amps:**

15.0 all mating ends all contact groupings

## Contact Maximum Ac Voltage Rating In Volts:

125.0 all mating ends all contact groupings

## **Polarization Method:**

Contact

Connector Locking Method:

Friction

### End Application:

Boatalt 49rc/

## Features Provided:

Grounded contact

## **Terminal Location:**

Side and back all mating ends all contact groupings

## **Terminal Type:**

Screw w/wire lock all mating ends all contact groupings

#### Shell Material:

Plastic

### **Included Contact Quantity:**

3 all mating ends all contact groupings

### Included Contact Type:

Flat socket all mating ends 2nd contact grouping

### **Product Name:**

Standard duplex receptacle

### **Special Features:**

Has built-in wire stripper and built-in wire looper. Has side wire terminals that accept up to no 10 solid or stranded wire and push-in terminals

that accept no 14 solid wire.

#### Color:

White

### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A039b0