NSN 5935-01-625-5867

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-625-5867 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.465 inches **Overall Height:** 1.453 inches **Overall Width:** 1.453 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** Between 0.556 inches and 0.587 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 20-16 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.1875 inches **Shell Material:** Aluminum alloy

Cadmium

Shell Surface Treatment:

NSN 5935-01-625-5867

Electrical Receptacle Connector Body - Page 2 of 2



Olive drab
Test Data Document:
81349-mil-dtl-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms3470 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A039b0

No

Color:

Mil-std (military Standard):

Mil-dtl-26482 spec.