

View Online at <https://aerobasegroup.com/nsn/5935-01-625-8040>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.405 inches

**Overall Height:**

1.328 inches

**Overall Width:**

1.328 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 1.057 inches and 1.067 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.057 inches and 1.067 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.431 inches and 0.462 inches

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-11 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

62.0

**Connector Locking Method:**

Bayonet pin

**End Application:**

Ic announcing

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

**Features Provided:**

Color band engagement indicator

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.0625 inches

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium

**Special Features:**

Has 3 equally spaced teeth for non-rotating purposes. Has fluid resistant insert with neoprene seals. Accommodates rear removable, crimp style, socket contacts.

**Color:**

Olive drab

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0