NSN 5935-01-625-9545

Connector Adapter - Page 1 of 2

(pbt) washers.



View Online at https://aerobasegroup.com/nsn/5935-01-625-9545

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 34.1 millimeters |
| Overall Diameter: |
| 17.0 millimeters |
| Distance From Mounting Shoulder To Front Face: |
| 20.3 millimeters |
| Threaded Device Type: |
| Mounting bushing |
| Mating End Quantity: |
| 2 |
| Contact Position Arrangement Style: |
| Bnc all mating ends |
| Connector Locking Method: |
| Bayonet pin and bayonet pin |
| End Application: |
| Ic announcing |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.50 inches |
| Contact Material: |
| Copper alloy all mating ends single contact grouping |
| Contact Surface Treatment: |
| Gold and nickel and copper all mating ends single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Nickel and copper |
| Included Contact Quantity: |
| 1 all mating ends single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round w/flat |
| Included Contact Type: |
| Coaxial socket all mating ends single contact grouping |
| Special Features: |
| The manufacturer is pan pacific but they do not have a valid cage code. This item includes 1 hex nut, 1 lock washer, and 2 white, plastic |
| |

NSN 5935-01-625-9545

Connector Adapter - Page 2 of 2



Precious Material And Location:

Contact plating gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0