

View Online at <https://aerobasegroup.com/nsn/5935-01-626-2297>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.174 inches

**Terminal Length:**

0.694 inches single mating end single contact grouping

**Overall Diameter:**

0.827 inches

**Environmental Protection:**

Dustproof

**Cable Entrance Diameter:**

0.291 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

N single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1500.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

11.0 gigahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded shell

**Connector Cable Strain Relief Method:**

Crimp type

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**End Application:**

Rg-8/u, 393/u cable

**Cable Opening Length:**

0.631 inches

**Thread Size:**

0.625 inches

**Terminal Location:**

Front single mating end single contact grouping

**Contact Material:**

Gold single mating end single contact grouping

**Crimping Tool Identifying Number:**

D

**Terminal Type:**

Quick disconnect, male single mating end single contact grouping

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Product Name:**

N crimp plug, connex-n connector

**Special Features:**

Vswr1.3 max, insulation resistance 5000 megohms

**Precious Material And Location:**

Contact pin gold

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0