

View Online at <https://aerobasegroup.com/nsn/5935-01-626-2297>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.174 inches

Terminal Length:

0.694 inches single mating end single contact grouping

Overall Diameter:

0.827 inches

Environmental Protection:

Dustproof

Cable Entrance Diameter:

0.291 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11.0 gigahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded shell

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

Rg-8/u, 393/u cable

Cable Opening Length:

0.631 inches

Thread Size:

0.625 inches

Terminal Location:

Front single mating end single contact grouping

Contact Material:

Gold single mating end single contact grouping

Crimping Tool Identifying Number:

D

Terminal Type:

Quick disconnect, male single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Product Name:

N crimp plug, connex-n connector

Special Features:

Vswr1.3 max, insulation resistance 5000 megohms

Precious Material And Location:

Contact pin gold

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0