

View Online at <https://aerobasegroup.com/nsn/5935-01-626-6785>

**Thread Class:**

2a and 2a and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

38.45 millimeters

**Overall Diameter:**

58.7 millimeters

**Distance From Mounting Shoulder To Front Face:**

22.6 millimeters

**Mounting Facility Thickness:**

Between 1.5 millimeters and 3.2 millimeters

**Threaded Device Type:**

Back shell and coupling facility and hub

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Size:**

37.0 millimeters and 1.625 inches and 44.0 millimeters

**Terminal Location:**

Back single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Thread Tolerance Class:**

6g external

**Included Contact Quantity:**

6 single mating end 2nd contact grouping

**Included Contact Type:**

Twisted pin 1st mating end 2nd contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material:**

Gold

**Thread Series Designator:**

Iso m and special acme and iso m

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0