NSN 5935-01-626-6785

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-626-6785 **Thread Class:** 2a and 2a and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 38.45 millimeters **Overall Diameter:** 58.7 millimeters **Distance From Mounting Shoulder To Front Face:** 22.6 millimeters **Mounting Facility Thickness:** Between 1.5 millimeters and 3.2 millimeters **Threaded Device Type:** Back shell and coupling facility and hub **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end all contact groupings Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 37.0 millimeters and 1.625 inches and 44.0 millimeters **Terminal Location:** Back single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Thread Tolerance Class:

6g external

Included Contact Quantity:

6 single mating end 2nd contact grouping

Included Contact Type:

Twisted pin 1st mating end 2nd contact grouping

Precious Material And Location:

Contact surface gold

NSN 5935-01-626-6785

Electrical Receptacle Connector - Page 2 of 2



| Precious Material: |
|-------------------------------------|
| Gold |
| Thread Series Designator: |
| Iso m and special acme and iso m $$ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A039b0