

NSN 5935-01-628-5854 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-628-5854 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.175 inches **Overall Diameter:** 3.116 inches **Unthreaded Mounting Hole Diameter:** 2.255 inches **Distance From Mounting Shoulder To Front Face:** 0.970 inches **Mounting Facility Thickness:** 0.128 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 36-7 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** 

Key or multiple key

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

**End Application:** 

2320-01-437-6957

Thready Qty Per Inch (tpi):

16 and 16

**Thread Size:** 

2.250 inches and 2.250 inches

**Terminal Location:** 

Back single mating end all contact groupings

**Terminal Type:** 

Crimp single mating end all contact groupings

## NSN 5935-01-628-5854

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Cadmium
Shell Surface Treatment:
Nickel
Included Contact Quantity:
7 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
Contacts per m39029/29-219 and -218
Color:
Olive drab
Precious Material And Location:
Contact surface silver and contact surfaces gold
Precious Material:
Silver and gold
Thread Series Designator:
Un and un
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-5015 spec.