## NSN 5935-01-628-7357

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-628-7357

**Thread Class:** 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.608 inches **Overall Diameter:** 1.386 inches **Distance From Mounting Shoulder To Front Face:** Between 0.861 inches and 0.882 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.125 inches **Threaded Device Type:** Back shell and coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 11-35 single mating end **Polarization Method:** Key or multiple key **Connector Locking Method:** Externally threaded shell **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Features Provided:** Color band engagement indicator and filter contact **Thread Size:** 15.0 millimeters and 0.7505 inches and 20.0 millimeters **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Thursd Talanana

Cadmium

Thread Tolerance Class: 6g external and 6g external

## NSN 5935-01-628-7357

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

13 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Special Features:** 

The finish is 500 hours salt spray resistant.

Color:

Olive drab

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0