NSN 5935-01-629-6850

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-629-6850 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 27.8 millimeters **Overall Height:** 28.6 millimeters **Overall Width:** 28.6 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 20.6 millimeters and 23.0 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 20.6 millimeters and 23.0 millimeters **Distance From Mounting Shoulder To Front Face:** 21.4 millimeters **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 13-35 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 68.0 and 178.0 and 204.0 and 247.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius **Thread Size:** 0.875 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Iron and nickel single mating end single contact grouping

NSN 5935-01-629-6850

A039b0

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
22 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Special acme
Specification Data:
81349-mil-dtl-38999/21 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: