Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-630-4775

| Thread Direction: | |
|-----------------------------------|--|
| Right-hand | |
| Overall Width: | |
| 0.940 inches | |
| Body Angle In Deg: | |
| 135.0 | |
| Distance From Centerline To | Connector End: |
| 0.440 inches | |
| Distance From Centerline To | Cable End: |
| 0.940 inches | |
| Cable Opening Quantity: | |
| 1 | |
| Size Designation: | |
| 13 | |
| Mounting Facility Type And | Quantity: |
| 1 threaded coupling | |
| Features Provided: | |
| Electromagnetic interference s | hielding |
| Thread Size: | |
| 18.0 millimeters | |
| Thread Tolerance Class: | |
| 6h internal | |
| Special Features: | |
| The finish is olive drab in color | and is 500 hours salt spray resistant. The backshell has rfi shielding and includes a spring. In the banding |
| area, there are two 0.250 by (| 0.170 slots. This item is similar to the image designated in the iig except it has no clamp. |
| Material: | |
| Aluminum alloy | |
| Surface Treatment: | |
| Cadmium and nickel | |
| Style Designator: | |
| Angle type w/clamp | |
| Thread Series Designator: | |
| lso m | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A10100 | |