## NSN 5935-01-631-0878

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-631-0878

**Thread Class:** 

2a and 2a and 2a

**Thread Direction:** 

Right-hand and right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

38.4 millimeters

**Overall Diameter:** 

52.4 millimeters

**Distance From Mounting Shoulder To Front Face:** 

22.6 millimeters

**Mounting Facility Thickness:** 

Between 1.5 millimeters and 3.2 millimeters

**Threaded Device Type:** 

Back shell and coupling facility and hub

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

21-75 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0 and 116.0 and 160.0 and 191.0 and 311.0

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

**Operating Tempurature Rating:** 

Between -65.0 degrees celsius and 175.0 degrees celsius

Thread Size:

31.0 millimeters and 1.375 inches and 38.0 millimeters

**Terminal Location:** 

Back single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

## NSN 5935-01-631-0878

Electrical Receptacle Connector - Page 2 of 2



Thread Tolerance Class:
6g external
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per mil-39029/90-529
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
lso m and special acme and iso m
Specification Data:
81349-mil-dtl-38999/24 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0