NSN 5935-01-631-3442

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-631-3442

| Body | Style: |
|------|--------|
|------|--------|

Straight shape duplex

Environmental Protection:

Weather resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

"3, 5-20" all mating ends

Contact Maximum Current Rating In Amps:

20.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 all mating ends all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Friction

End Application:

Stms trailer

Operating Tempurature Rating:

Between -35.0 degrees celsius and 66.0 degrees celsius

Features Provided:

Grounded contact and w/circuit protection device

Terminal Location:

Back and side all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Terminal Type:

Screw w/wire lock all mating ends all contact groupings

Shell Material:

Plastic polycarbonate

Included Contact Quantity:

3 all mating ends all contact groupings

Included Contact Type:

T-socket all mating ends 1st contact grouping

Product Name:

Gfci receptacle, 20 amp

Special Features:

Accommodates 14 - 10 awg wire.

Color:

White

Shelf Life:

N/a

NSN 5935-01-631-3442

Electrical Receptacle Connector - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A039b0