## NSN 5935-01-646-2730

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-646-2730

**Body Style:** 

Straight shape w/flange w/cover

**Overall Length:** 

3.40 inches

**Bushing Diameter:** 

2.46 inches

**Distance Between Mounting Facility Centers:** 

2.41 inches

**Distance From Mounting Shoulder To Rear Face:** 

2.36 inches

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

L5-30 single mating end

**Contact Maximum Current Rating In Amps:** 

30.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

125.0 single mating end single contact grouping

**Polarization Method:** 

Contact

**Connector Locking Method:** 

Contact twistlock

**End Application:** 

Boatalt 35wb/

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Nickel single mating end single contact grouping

**Terminal Type:** 

Screw single mating end single contact grouping

**Shell Material:** 

Plastic polyester and plastic polyamide

**Included Contact Quantity:** 

3 single mating end single contact grouping

**Included Contact Type:** 

Curved pin w/inside lip single mating end 1st contact grouping

**Special Features:** 

Cage 1gfc6 is type f but they hold design control on p/n

Color:

White

## NSN 5935-01-646-2730

Electrical Receptacle Connector - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0