NSN 5935-01-646-9270

Electrical Receptacle Connector Body - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-646-9270 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.248 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.873 inches and 0.883 inches |
| Mounting Facility Thickness: |
| Between 0.062 inches and 0.125 inches |
| Threaded Device Type: |
| Coupling facility and mounting bushing and back shell |
| Mating End Quantity: |
| 1 |
| Polarization Method: |
| Keyway or multiple keyway |
| Connector Locking Method: |
| Externally threaded shell |
| Connector Cable Strain Relief Method: |
| Shrinkable tubing |
| End Application: |
| V-22 aircraft |
| Features Provided: |
| Color band engagement indicator |
| Thread Size: |
| 1.625 inches and 44.0 millimeters and 37.0 millimeters |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Thread Tolerance Class: |
| 6g external and 6g external |
| Bushing Accommodation Hole Shape: |
| Round |
| Special Features: |
| Accommodates quadrax sockets. |
| Thread Series Designator: |
| lso m |
| Shelf Life: |

N/a

NSN 5935-01-646-9270

Electrical Receptacle Connector Body - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

A039b0